Yuasa Technical Data Sheet

Yuasa RE7-12LFR Industrial VRLA Battery

Specifications

Nominal voltage (V) 12 10-hr rate Capacity to 1.8V/Cell at 20°C (Ah) 6.2 20-hr rate Capacity to 1.75V/Cell at 20°C (Ah) 7

Dimensions

Length (mm) $151 (\pm 1)$ Width (mm) $65 (\pm 1)$ Height (mm) $94 (\pm 1)$ Height over terminals (mm) $97,5 (\pm 1)$ Mass (kg)2.75

Terminal Type

FASTON - Quickfit / release (IST where stated) 6.35

Operating Temperature Range

Storage (in fully charged condition) -15°C to $+45^{\circ}\text{C}$ Charge -15°C to $+45^{\circ}\text{C}$ Discharge -15°C to $+45^{\circ}\text{C}$

Storage

Capacity loss per month at 20°C (% approx.)

Case Material

Standard ABS (UL94:V0)

Charge Voltage

Float charge voltage at 20°C (V)/Block 13.65 (\pm 1%) Float charge voltage at 20°C (V)/Cell 2.275 (\pm 1%)

Float Chg voltage tmp correction factor from std -3

20°C (mV)

Cyclic (or Boost) charge Voltage at 20° C (V)/Block 14.5 ($\pm 3\%$) Cyclic (or Boost) charge Voltage at 20° C (V)/Cell 2.42 ($\pm 3\%$)

Cyclic Chg voltage tmp correction factor from std -4

20°C (mV)

Charge Current

Float charge current limit (A) No limit Cyclic (or Boost) charge current limit (A) 1.75

Maximum Discharge Current

1 second (A) 105 1 minute (A) 42

Impedance

Measured at 1 kHz ($m\Omega$) 35


Design Life & Approvals

EUROBAT Classification: General Purpose 6 to 9 years Yuasa design life at 20°C (yrs) up to 10 years





Layout



3rd Party Certifications

ISO9001 - Quality Management Systems UNDERWRITERS LABORATORIES Inc.





Safety

Installation

Can be installed and operated in any orientation except permanently inverted.

Handles

Batteries must not be suspended by their handles (where fitted).

Vent valves

Each cell is fitted with a low pressure release valve to allow gasses to escape and then reseal.

Gas release

VRLA batteries release hydrogen gas which can form explosive mixtures in the air. Do not place inside a sealed container.

Recycling

YUASA's VRLA batteries must be recycled at the end of life in accordance with local and national laws and regulations.







