

Yuasa Technical Data Sheet

* Due to unprecedented demand following the easing of COVID-19 lockdown measures, this product may be supplied without a state of charge indicator and not conform to the level of roll over protection advertised. Product performance and quality are not affected by this. Please check battery labels for specification details.

Yuasa YBX7110 - YBX7000 EFB Start Stop Plus Batteries

Performance

Voltage12VCapacity (20-hour)75AhCold Cranking Amps (EN1)730A

Dimensions

Length	317mm
Width	175mm
Height	175mm

Weights & Measures

Mean Weight with Acid

19.8kg

Container Features

Case Type	LB4 DIN EFB
Hold Down	B3
State of Charge Indicator	✓
Handles	✓
End Venting	✓
Lid Type	SMF Double Lid



Technology

Flame Arrestor	✓
Technology	Ca/Ca
Separator	PE
VDA Roll Over Test	✓
Recommended Charge Rate	4A
Performance Marking	W3-C2-V3-M2

Terminal TypeCell Assembly LayoutBattery Hold-downT1
Standard DIN Post $\overbrace{0}^{\#}$ $\overbrace{0}^{\#}$ $\overbrace{0}^{\#}$ $\overbrace{0}^{\#}$ $\overbrace{0}^{\#}$ $\overbrace{0}^{\#}$ $\overbrace{0}^{\#}$ Positive TerminalNegative TerminalNegative Terminal

Data Sheet generated on 26/04/2024 – E&OE

The world's leading battery manufacturer

YUAS/